

Basic Facts

HOUSE BUILT: 1934

HOUSE RENOVATED: 2005/6

WORKS CARRIED OUT:

- Floors, external walls and roof heavily insulated
- New double glazed timber windows
- Solar thermal panels for hot water
- Natural flooring throughout
- Low energy lighting
- Low water use

CO2 REDUCTION (OHSB calculation 2009):

- Before: 15.6 tonnes of CO2 per year
- After: 4.7 tonnes CO2 per year = 70% reduction

Eco-Renovation Features

1. External Works:

- Existing compost
- Gardening/recycling garden 'waste'
- Fence posts & doors
- Willow fences
- Porous paving
- Existing herb garden
- New vegetable garden
- Heat treated timber cladding
- Green oak canopy over deck
- Reclaimed timber decking
- Aluminium rainwater goods

2. External Envelope:

- Airtightness test
- New high performance timber windows
- Cellulose insulation under flooring
- 2x insulation in roof with breather membrane
- 80mm external wall insulation and render
- Draft proofing front door

3. Heating/hot water:

- Gas condensing boiler
- Solar panels
- Passive solar/conservatory

4. Lighting:

- Use of natural light
- LED/compact fluorescent lighting

5. Interior finishes:

- Natural & clay paints
- Reuse of existing floorboards on 1st floor
- Reuse of existing 1930's interior doors
- Reclaimed flooring on ground floor with natural oil finish
- Slate, sea grass, linoleum

6. Water:

- Dual flush WC's
- Low flow shower
- Water butts outside

7. Waste:

- Bristol Wood recycling project
- Firewood
- Garden waste
- Skips
- Yard sale
- Cardboard packaging

Eco-Renovation Features

8. Technical data available:

- Architects drawings – existing and proposed
- Construction details of external envelope (walls, floor and roof) – before and after
- Photos (before and after)
- U-values (before and after)

11. Lifestyle

- No tumble dryer
- Open fire
- Veggie box

March 2010

9. Data collected after occupation:

- Airtightness test
- Thermographic imaging
- 12 months of bills (water, gas and electricity)
- 12 months temperature logging with graphs illustrating the outcomes
- 12 months solar thermal panel output
- Energy Performance Certificate
- SAP rating
- NHER rating

10. Other post occupancy information:

- Food growing
- Waste reduction
- Transport

Before and after


	BEFORE	AFTER
WALLS	225MM SOLID WALLS WITH WHITE EXTERNAL RENDER (U-VALUE=+/- 2W/m2K)	80MM POLYISOCYANURATE INSULATION ON TOP OF EXISTING RENDER + NEW RENDER SYSTEM(U-VALUE=+/- 0.22W/m2K)
GROUND FLOOR	NO INSULATION	150MM CELLULOSE INSULATION + AIRTIGHT MEMBRANE
ROOF	NO INSULATION	200MM MINERAL WOOL INSULATION (BETWEEN AND ABOVE RAFTERS) + AIRTIGHT MEMBRANE
WINDOWS	ORIGINAL METAL SINGLE GLAZED FRAMES	DOUBLE GLAZED, LOW E COATED, ARGON FILLED TIMBER FRAME WINDOWS BY RATIONEL
HEATING	GAS BOILER AND SINGLE PANEL RADIATORS WITH ELECTRIC HEATER BACK-UP	VAILLANT ECOTEC GAS CONDENSING BOILER WITH DOUBLE PANEL FIN RADIATORS
HOT WATER	IMMERSION HEATER	4M2 SOLAR THERMAL PANELS FROM MAY-SEPTEMBER, BOILER FOR REMAINDER OF YEAR
LIGHTING	ALL INCANDESCENT BULBS	MIXTURE OF LED'S, COMPACT FLUORESCENT & HALOGEN/INCANDESCENT
WATER	13 LITRE WC'S	LOW FLUSH, DUAL FLUSH WC'S, WATER BUTTS & BEHAVIOUR
WASTE	UNKNOWN	UNCOOKED ORGANIC MATTER IN COMPOST; COOKED FOOD, CARDBOARD ETC TO MUNICIPAL WASTE COLLECTION; PLASTIC TO 'REFRESCO' BINS; REUSABLE CONTAINERS & BAGS
FLOORING	CARPET THROUGHOUT PLUS VINYL IN BATHROOMS/KITCHEN	RECLAIMED TIMBER ON GROUND FLOOR; EXISTING BOARDS ON 1 ST FLOOR; NEW FRENCH OAK ON 2 ND FLOOR; LINOLEUM AND SLATE IN BATHROOMS & UTILITY ROOM.
PAINTS	UNKNOWN	CLAY, NATURAL AND CONVENTIONAL PAINTS

External Envelope details

NOTE: Materials are listed from inside to outside

- **External walls: wet plaster; 225mm original brickwork; 80mm polyisocyanurate insulation boards; 3 coat render system**
- **Chimney breasts and first floor of front elevation (with wall hung tile external finish) internally lined with 20mm foam backed plasterboard**
- **Ground floor: reclaimed T&G timber floor boards; airtight waterproof membrane lapped up sides of all external walls; 150mm cellulose insulation in between joists; breather membrane holding insulation in.**
- **Roof: plasterboard; airtight waterproof membrane; 100mm Rockwool underlay insulation between rafters; 70mm Rockwool overlay board on top of rafters; Tyvek breather membrane; original clay tiles reused.**
- **All windows by Rationel: double glazed, low e coated Argon filled cavity.**
- **Front door: original with double layer of draught proofing and foam backed plasterboard within panels of door on inside.**

Energy consumption over 12 months



Energy consumption for 29 Redland Hill


- Average m² of typical 3 bedroom house 89 m² (Energy Savings Trust)
- 29 Redland Hill = 216 m² = 2.4 times larger than the average house
- Typical **GAS** consumption for a 3 bedroom house: 16,000 kWh* x 2.4 = 38,400 kWh
- Typical **ELECTRICITY** consumption for a 3 bedroom house: 4,800 (5,480 kWh)* x 2.4 = 11,520 kWh
- Typical **GAS** consumption for 29 Redland Hill including office: 15,308 kWh
- Typical **ELECTRICITY** consumption for 29 Redland Hill including office: 4959 kWh
- Typical **GAS** consumption for offices = 79 kWh/m²** x 40m² (say) = 3160m²
- Typical **ELECTRICITY** consumption for offices = 54 kWh/m²** x 40m² (say) = 2160 kWh
- Typical **GAS** consumption for 29 Redland Hill excluding office: 15,308 - 3160 = 12,148 kWh
- Typical **ELECTRICITY** consumption for 29 Redland Hill excluding office: 4959 - 2160 = 2799 kWh

*Energy Saving Trust (Strathclyde University) figures ** CIBSE Guide F

29Redland Hill.

All information presented here is for guidance only.
archipeleco architects take no responsibility for any action arising from others using this information.

Solar thermal panels



29 Redland Hill.

All information presented here is for guidance only.


archipeleco architects take no responsibility for any action arising from others using this information.

Photovoltaic panels



7 photovoltaic panels were installed on 1st September 2010 with an installed capacity of 1225W – about a quarter of the total electricity demand of the house and home office with three people.


Temperature swings over a 24 hour period



29 Redland Hill.

All information presented here is for guidance only.
archipeleco architects take no responsibility for any action arising from others using this information.


Thermal mass



29 Redland Hill.

All information presented here is for guidance only.
archipeleco architects take no responsibility for any action arising from others using this information.




A week away at Christmas



29 Redland Hill.

All information presented here is for guidance only.
archipeleco architects take no responsibility for any action arising from others using this information.

Thermographic images



29 Redland Hill.

All information presented here is for guidance only.

archipeleco architects take no responsibility for any action arising from others using this information.

Low energy lighting

Light Type	Typical Efficacy (lm/W)	Usable optical Light (lm/W)	Lifetime (hours)
Incandescent	17	10-17	3000
Halogen / HPL	20 / 25	12-20	10,000
T12 fluorescent	60	45-50	20,000
Compact Fluorescent	62	31	10,000
Metal halide	70	<40	< 15,000
T8 fluorescent	74	55-60	20,000
High-pressure sodium	91	<50	< 24,000
T5 fluorescent	100	80	20,000
Best High Power white LED in 2007	105	85	> 50,000
Low-pressure sodium	120	65-70	18,000
Record LED -	150	120	TRD



Water



Average water consumption per person in the UK

= 150 litres/day

Average water consumption per person at 29 Redland Hill

= 71 litres/day

Achieved through:


- Showers not baths & low flow shower heads
- Low flush dual flush WC's (and not flushing every use!)
- Rainwater harvesting for garden irrigation
- Water meter

29Redland Hill.

All information presented here is for guidance only.

archipeleco architects take no responsibility for any action arising from others using this information.

Conservatory



29 Redland Hill.

All information presented here is for guidance only.

archipeleco architects take no responsibility for any action arising from others using this information.

External works

- Existing & new compost bins (from pallets)
- Gardening/recycling garden 'waste'
- Willow hurdles
- Existing herb garden
- New vegetable garden
- Heat treated timber cladding
- Green oak canopy over deck
- Reclaimed timber decking
- Aluminium rainwater goods

External works

- Porous paving..?